

PATENT ABSTRACTS

9/3,K/2 (Item 2 from file: 350) [Links](#)

Fulltext available through: [Order File History](#)

Derwent WPIX

(c) 2008 The Thomson Corporation. All rights reserved.

0013330458 & *Drawing available*

WPI Acc no: 2003-417853/200339

XRPX Acc No: N2003-333255

Communication network capacity management method involves selecting allocation capacity having maximum weighted combination of expected revenue and risk

Patent Assignee: MITRA D (MITR-I); RAMAKRISHNAN K G (RAMA-I); WANG Q (WANG-I);

LUCENT TECHNOLOGIES INC (LUCI)

Inventor: MITRA D; RAMAKRISHNAN K G; WANG Q

Patent Family (2 patents, 1 & countries)

| Patent Number | Kind | Date | Application Number | Kind | Date | Update | Type |
|----------------|------|----------|--------------------|------|----------|--------|------|
| US 20030035429 | A1 | 20030220 | US 2001295614 | P | 20010604 | 200339 | B |
| | | | US 2002163140 | A | 20020604 | | |
| US 7123588 | B2 | 20061017 | | | | 200668 | E |

Priority Applications (no., kind, date): US 2001295614 P 20010604; US 2002163140 A 20020604

Patent Details

| Patent Number | Kind | Lan | Pgs | Draw | Filing Notes | |
|----------------|------|-----|-----|------|------------------------|---------------|
| US 20030035429 | A1 | EN | 12 | 4 | Related to Provisional | US 2001295614 |

Original Publication Data by AuthorityArgentinaPublication No. ...Original Abstracts:framework of the invention also incorporates, as a parameter, the provision of link capacity to other network service providers in the determination of an optimal resource allocation. In a preferred embodiment of the invention, such an optimal resource allocation is determined... ...Claims:plurality of nodes, wherein pairs of said nodes are connected by one or more physical paths, each said path including one or more connected links, and wherein ownership of said links is divided among a plurality of entities...

9/3,K/5 (Item 5 from file: 350) [Links](#)

Fulltext available through: [Order File History](#)

Derwent WPIX

(c) 2008 The Thomson Corporation. All rights reserved.

0009401435 & *Drawing available*

WPI Acc no: 1999-337577/199928

XRPX Acc No: N1999-253001

Calling line resold to service provider service routing system

Patent Assignee: BELL SOUTH INTELLECTUAL PROPERTY CORP (BELL-N)

Inventor: BEDINGFIELD J C; HOLT S C; LAPIERRE S R

Patent Family (3 patents, 82 & countries)

| Patent Number | Kind | Date | Application Number | Kind | Date | Update | Type |
|---------------|------|----------|--------------------|------|----------|--------|------|
| WO 1999023808 | A1 | 19990514 | WO 1998US23443 | A | 19981104 | 199928 | B |
| AU 199913041 | A | 19990524 | AU 199913041 | A | 19981104 | 199940 | E |
| EP 1036462 | A1 | 20000920 | EP 1998956539 | A | 19981104 | 200047 | E |
| | | | WO 1998US23443 | A | 19981104 | | |

Priority Applications (no., kind, date): US 199764230 P 19971104

Patent Details

| Patent Number | Kind | Lan | Pgs | Draw | Filing Notes | |
|-------------------------------------|---|-----|-----|------|---------------------|----------------|
| WO 1999023808 | A1 | EN | 27 | 9 | | |
| National Designated States,Original | AL AM AT AU AZ BA BB BG BR BY CA CH CN CU CZ DE DK EE ES FI GB GD GE GH GM HR HU ID IL IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MD MG MK MN MW MX NO NZ PL PT RO RU SD SE SG SI SK SL TJ TM TR TT UA UG US UZ VN YU ZW | | | | | |
| Regional Designated States,Original | AT BE CH CY DE DK EA ES FI FR GB GH GM GR IE IT KE LS LU MC MW NL OA PT SD SE SZ UG ZW | | | | | |
| AU 199913041 | A | EN | | | Based on OPI patent | WO 1999023808 |
| EP 1036462 | A1 | EN | | | PCT Application | WO 1998US23443 |
| | | | | | Based on OPI patent | WO 1999023808 |
| Regional Designated States,Original | AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE | | | | | |

Original Publication Data by AuthorityArgentinaPublication No. ...Original Abstracts:a trunk group. The AIN or non-AIN switch may access a line class code table (160-164) to determine the proper routing information. Calls made from resold lines are routed to the AIN hub... ... accesses a database (675) containing directory numbers for resold lines and identifiers for competitive service providers. Once the carrier is located, additional tables may be accessed to determine the routing information specified by the carrier for handling the call. The routing information... ... a trunk group. The AIN or non-AIN switch may access a line class code table (160-164) to determine the proper routing information. Calls made from resold lines are routed to the AIN hub (190). Once the call is... ... directory numbers for resold lines and identifiers for competitive service providers. Once the carrier is located, additional tables may be accessed to determine the routing information specified by the carrier for handling the call. The routing information is transmitted by the SCP...

9/5/7 (Item 7 from file: 350) [Links](#)

Fulltext available through: [Order File History](#)

Derwent WPIX

(c) 2008 The Thomson Corporation. All rights reserved.

0008622587 & *Drawing available*

WPI Acc no: 1998-159032/199814

XRPX Acc No: N1998-126455

Automatic access code dialling method - involves providing dialler which establishes connection to network with number provided network with or without access code according to comparison with pre-stored list

Patent Assignee: LUCENT TECHNOLOGIES INC (LUCE)

Inventor: JOHNSON J E

Patent Family (1 patents, 1 & countries)

| Patent Number | Kind | Date | Application Number | Kind | Date | Update | Type |
|---------------|------|----------|--------------------|------|----------|--------|------|
| US 5719931 | A | 19980217 | US 1995549612 | A | 19951027 | 199814 | B |

Priority Applications (no., kind, date): US 1995549612 A 19951027

Patent Details

| Patent Number | Kind | Lan | Pgs | Draw | Filing Notes |
|---------------|------|-----|-----|------|--------------|
| US 5719931 | A | EN | 6 | 3 | |

Alerting Abstract US A

The access code dialling method involves providing an access code dialler which establishes a connection between a telephone communication device and a communication network. The connection is automatically broken using the access code dialler. A user entered telephone number received from the telephone communication device is stored in the access code dialler.

At least a portion of the stored number is compared to a list of numbers. The stored number is provided to the communication network without an access code if the list does not contain the portion of the stored number compared to the list of numbers and with an access code if it does. The connection between the telephone communication device and the communication network is automatically re-established using the access code dialler.

ADVANTAGE - Automatically determines alternative service provider using table in memory.

[bad date?]

10/3,K/2 (Item 2 from file: 350) [Links](#)

Fulltext available through: [Order File History](#)

Derwent WPIX

(c) 2008 The Thomson Corporation. All rights reserved.

0013442290

WPI Acc no: 2003-533480/200351

XRPX Acc No: N2003-423226

Network organizing method based on multi protocol label exchange virtual private network

Patent Assignee: HUAWEI TECH CO LTD (HUAW-N); HUAWEI TECHNOLOGIES CO LTD (HUAW-N); XUE G (XUEG-I)

Inventor: SUU G; XUE G

Patent Family (6 patents, 34 & countries)

| Patent Number | Kind | Date | Application Number | Kind | Date | Update | Type |
|----------------|------|----------|--------------------|------|----------|--------|------|
| CN 1414753 | A | 20030430 | CN 2002125817 | A | 20020805 | 200351 | B |
| EP 1388978 | A1 | 20040211 | EP 2002102573 | A | 20021113 | 200411 | E |
| US 20040025054 | A1 | 20040205 | US 2003393931 | A | 20030320 | 200411 | E |
| JP 2004072708 | A | 20040304 | JP 2002361535 | A | 20021212 | 200417 | E |
| AU 2002320665 | A1 | 20040219 | AU 2002320665 | A | 20021220 | 200445 | E |
| CN 1183726 | C | 20050105 | | | | 200620 | E |

Priority Applications (no., kind, date): CN 2002125817 A 20020805

Patent Details

| Patent Number | Kind | Lan | Pgs | Draw | Filing Notes |
|-------------------------------------|---|-----|-----|------|--------------|
| CN 1414753 | A | ZH | | 0 | |
| EP 1388978 | A1 | EN | | | |
| Regional Designated States,Original | AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR IE IT LI LT LU LV MC MK NL PT RO SE SI SK TR | | | | |
| JP 2004072708 | A | JA | 9 | | |

...Original Titles:MPLS/BGP VPN gateway-based networking method Alerting Abstract ...exchange between the network of local internet inserting service person (ISP) and one level higher ISP network or other ISP network, connecting MPLS VPN gate way with the local ISP network according to the network technical conformation, connecting MPLS VPN gate way with one level higher or other ISP network, and at the same time, connecting MPLS VPN gate way with the equipment of... Original Publication Data by AuthorityArgentinaPublication No. ...Original Abstracts:a local Internet Service Provider (ISP) network and a superior Internet Service Provider (ISP) network/other Internet Service Provider (ISP) network, connect the Multi Protocol Label Switching Virtual Private Network (MPLS VPN) gateway with the local Internet Service Provider (ISP) network and the superior Internet Service Provider (ISP) network/other Internet Service Provider (ISP) network and at the same time connect the Multi Protocol Label Switching Virtual Private Network (MPLS VPN) gateway... The present invention discloses a MPLS/BGP VPN gateway-based network method comprising: interposing one or more Multi Protocol Label Switching Virtual Private Network (MPLS VPN) gateways between a first ISP network and a second ISP network, connecting the MPLS/BGP VPN gateway with the first ISP network and the second ISP network and at the same time connect the MPLS/BGP VPN gateway with a Custom Edge Router (CE) in the first ISP subscriber's network, and activating protocol transmissions on the MPLS/BGP VPN gateway to provide MPLS/BGP VPN services. The present invention enables ISPs to provide MPLS/BGP VPN

services quickly with low investment and make use of conventional network without comprehensive reconstruction, which enhances competitive power and protect conventional investment. ...Claims:a local Internet Service Provider (ISP) network and a superior Internet Service Provider (ISP) network/other Internet Service Provider (ISP) network;step 2: connecting the Multi Protocol Label Switching Virtual Private Network (MPLS VPN) gateway with the local Internet Service Provider (ISP) network and the superior Internet Service Provider (ISP) network/other Internet Service Provider (ISP) network and connecting the Multi Protocol Label Switching Virtual Private Network (MPLS VPN) gateway with a Custom Edge Router (CE... ... What is claimed is:1. A MPLS/BGP VPN gateway-based networking method enabling private communications between subscribers of a first ISP network and subscribers of a second ISP network, comprising the steps:i) interposing at least one MPLS/BGP VPN gateway between the first ISP network and the second ISP network to construct a virtual private network (VPN) with Multiprotocol Label Switching (MPLS) capabilities using Border Gateway Protocol (BGP) wherein the MPLS/BGP VPN gateway provides MPLS/BGP VPN services;ii) connecting the MPLS/BGP VPN gateway with the first ISP network and the second ISP network;iii) connecting the MPLS/BGP VPN gateway to a CE in the subscriber's network;iv) activating protocol transmissions on the MPLS/BGP VPN gateway to provide MPLS/BGP VPN services.

10/3,K/3 (Item 3 from file: 350) [Links](#)

Fulltext available through: [Order File History](#)

Derwent WPIX

(c) 2008 The Thomson Corporation. All rights reserved.

0012459471 & *Drawing available*

WPI Acc no: 2002-405434/200243

Related WPI Acc No: 2002-372317; 2002-372318; 2002-372321; 2002-372322; 2002-383519; 2002-435588; 2003-646412; 2004-774509

XRPX Acc No: N2002-318295

Performance and cost optimization in inter-network allowing performance data about routes to be exchanged between routers

Patent Assignee: BALDONADO O C (BALD-I); FINN S P (FINN-I); KARAM M J (KARA-I); LLOYD M A (LLOY-I); MADAN H S (MADA-I); MCGUIRE J G (MCGU-I); ROUTESCENCE TECHNOLOGIES INC (ROUT-N); VILLAVERDE J P (VILL-I)

Inventor: BALDONADO O C; FINN S P; KARAM M J; LLOYD M A; MADAN H S; MCGUIRE J G; VILLAVERDE J M P; VILLAVERDE J P

Patent Family (5 patents, 96 & countries)

| Patent Number | Kind | Date | Application Number | Kind | Date | Update | Type |
|----------------|------|----------|--------------------|------|----------|--------|------|
| WO 2002033894 | A2 | 20020425 | WO 2001US32312 | A | 20011017 | 200243 | B |
| US 20020078223 | A1 | 20020620 | US 2000241450 | P | 20001017 | 200244 | E |
| | | | US 2001275206 | P | 20010312 | | |
| | | | US 2001923924 | A | 20010806 | | |
| AU 200213287 | A | 20020429 | AU 200213287 | A | 20011017 | 200255 | E |
| EP 1356634 | A2 | 20031029 | EP 2001981657 | A | 20011017 | 200379 | E |
| | | | WO 2001US32312 | A | 20011017 | | |
| AU 2002213287 | A8 | 20051013 | AU 2002213287 | A | 20011017 | 200611 | E |

Priority Applications (no., kind, date): US 2000241450 P 20001017; US 2001275206 P 20010312; US 2001903423 A 20010710; US 2001903441 A 20010710; US 2001923924 A 20010806

Patent Details

| Patent Number | Kind | Lan | Pgs | Draw | Filing Notes | |
|-------------------------------------|---|-----|-----|------|------------------------|----------------|
| WO 2002033894 | A2 | EN | 40 | 6 | | |
| National Designated States,Original | AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CO CR CU CZ DE DK DM DZ EC EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ PH PL PT RO RU SD SE SG SI SK SL TJ TM TR TT TZ UA UG US UZ VN YU ZA ZW | | | | | |
| Regional Designated States,Original | AT BE CH CY DE DK EA ES FI FR GB GH GM GR IE IT KE LS LU MC MW MZ NL OA PT SD SE SL SZ TR TZ UG ZW | | | | | |
| US 20020078223 | A1 | EN | | | Related to Provisional | US 2000241450 |
| | | | | | Related to Provisional | US 2001275206 |
| AU 200213287 | A | EN | | | Based on OPI patent | WO 2002033894 |
| EP 1356634 | A2 | EN | | | PCT Application | WO 2001US32312 |
| | | | | | Based on OPI patent | WO 2002033894 |
| Regional Designated States,Original | AL AT BE CH CY DE DK ES FI FR GB GR IE IT LI LT LU LV MC MK NL PT RO SE SI TR | | | | | |
| AU 2002213287 | A8 | EN | | | Based on OPI patent | WO 2002033894 |

Alerting Abstract ... USE - For supporting routing intelligence (Stationed at ISP, government organization, university, or other organization supporting a sub-network coupled to an inter-network) for evaluating routing paths based on... Original Publication Data by AuthorityArgentinaPublication No. ...Original Abstracts:effecting any changes to routing. Routing decisions may be injected to the edge routers via BGP updates. The devices may be stationed at the premises of a multihomed organization, such as an enterprise, ISP, government organization, university, or other organization supporting a sub-network coupled to an internetwork. In other embodiments, the routing intelligence... ... effecting any changes to routing. Routing decisions may be injected to the edge routers via BGP updates. The devices may be stationed at the premises of a multihomed organization, such as an enterprise, ISP, government organization, university, or other organization... ... effecting any changes to routing. Routing decisions may be injected to the edge routers via BGP updates. The devices may be stationed at the premises of a multihomed organization, such as an enterprise, ISP, government organization, university, or other organization supporting a sub-network coupled to an internetwork. In other embodiments, the routing intelligence comprises processes executed on a router... ... de routage peuvent etre injectees dans les routeurs de bordure via des mises a jour BGP. Les dispositifs peuvent etre implantes dans les locaux d'une organisation a plusieurs sieges, telle qu'une entreprise, un fournisseur de services Internet, une organisation gouvernementale, une universite, ou une autre organisation supportant un...

FULL-TEXT PATENTS

[your application]

15/3K/10 (Item 5 from file: 349) [Links](#)

Fulltext available through: [Order File History](#)

PCT FULLTEXT

(c) 2008 WIPO/Thomson. All rights reserved.

01098243

A METHOD AND A SYSTEM FOR PERFORMING CONNECTIVITY EVALUATIONS ON
DATA COMMUNICATION NETWORKS AND RELATED INFORMATION TECHNOLOGY
PRODUCT

PROCEDE ET SYSTEME POUR EVALUATIONS DE CONNECTIVITE SUR RESEAUX DE
TRANSMISSION DE DONNEES, ET PRODUIT DE TECHNOLOGIE DE L'INFORMATION ASSOCIE

Patent Applicant/Patent Assignee:

- TELECOM ITALIA S P A; Piazza degli Affari, 2, I-20123 Milano
IT; IT(Residence); IT(Nationality)
(For all designated states except: US)
- CORRADO Alessandro; Via di Nanni, 38A, I-10042 Nichelino
IT; IT(Residence); IT(Nationality)
(Designated only for: US)
- LAROSA Giuseppe; Strada Bairo, 9, I-10081 Castellamonte
IT; IT(Residence); IT(Nationality)
(Designated only for: US)
- ROSSI Gianni; Telecom Italia S.p.A, Via G. Reiss Romoli, 274, I-10148 Torino
IT; IT(Residence); IT(Nationality)
(Designated only for: US)
- VERCELLONE Vinicio; Telecom Italia S.p.A., Via G. Reiss Romoli, 274, I-10148 Torino
IT; IT(Residence); IT(Nationality)
(Designated only for: US)

Patent Applicant/Inventor:

- CORRADO Alessandro
Via di Nanni, 38A, I-10042 Nichelino; IT; IT(Residence); IT(Nationality); (Designated only for: US)
- LAROSA Giuseppe
Strada Bairo, 9, I-10081 Castellamonte; IT; IT(Residence); IT(Nationality); (Designated only for: US)
- ROSSI Gianni
Telecom Italia S.p.A, Via G. Reiss Romoli, 274, I-10148 Torino; IT; IT(Residence); IT(Nationality);
(Designated only for: US)
- VERCELLONE Vinicio
Telecom Italia S.p.A., Via G. Reiss Romoli, 274, I-10148 Torino; IT; IT(Residence); IT(Nationality);
(Designated only for: US)

Legal Representative:

- GIANNESI Pier Giovanni(et al)(agent)
Pirelli & C. S.p.A., Viale Sarca, 222, I-20126 Milano; IT;

| | Country | Number | Kind | Date |
|-------------|---------|------------|------|----------|
| Patent | WO | 200421650 | A1 | 20040311 |
| Application | WO | 2003EP9692 | | 20030901 |
| Priorities | IT | 2002TO762 | | 20020902 |

Designated States: (All protection types applied unless otherwise stated - for applications 2004+)

[EP] AT; BE; BG; CH; CY; CZ; DE; DK; EE; ES;
FI; FR; GB; GR; HU; IE; IT; LU; MC; NL;
PT; RO; SE; SI; SK; TR;

[OA] BF; BJ; CF; CG; CI; CM; GA; GN; GQ; GW;
ML; MR; NE; SN; TD; TG;

[AP] GH; GM; KE; LS; MW; MZ; SD; SL; SZ; TZ;
UG; ZM; ZW;

[EA] AM; AZ; BY; KG; KZ; MD; RU; TJ; TM;

Publication Language: English
Filing Language: English
Fulltext word count: 6800

Detailed Description:

...according to the invention makes resort
to the databases essentially formed by the so called BGP
tables and/or by similar tables, generically denoted by
BGP11 ... , BGPm, in Figure 2. These... ..derived from
subjects toward which the connectivity evaluation must
be mainly performed (i.e. the candidate ISPs 14) in
other terms they may be still derived from the ISP
suppliers 12.

It is therefore evident... ..the solution according to the invention can be
applied by using either the strictly defined BGP tables
or by tables structurally similar or functionally
equivalent to the BGP tables under question: for this
reason in the claims which follow, reference will be
generally... ..by
102, 'the system S carries out the extraction of the
information contained in the BGP tables denoted by the
references BGP11 to BGPml.

15/3K/16 (Item 11 from file: 349) [Links](#)
Fulltext available through: [Order File History](#)

PCT FULLTEXT

(c) 2008 WIPO/Thomson. All rights reserved.

00856131

COMMUNICATION SYSTEM AND METHOD
SYSTEME ET PROCEDE DE COMMUNICATION

Patent Applicant/Patent Assignee:

- BAND-X LIMITED; 26th Floor, Millbank Tower, 21-24 Millbank, London SW1P 4QP
GB; GB(Residence); GB(Nationality)
(For all designated states except: US)
- DE FERRANTI Marcus; 20 Gilston Road, London SW10 9SR
GB; GB(Residence); GB(Nationality)
(Designated only for: US)
- ELLIOT Richard John; 74 Limerston Street, London SW7 0HJ
GB; GB(Residence); GB(Nationality)
(Designated only for: US)
- PANTER Nigel; 19 Reculver Road, Herne Bay CT6 6LG
GB; GB(Residence); GB(Nationality)
(Designated only for: US)
- PANTER Timothy; 12 Filton Road, Horsfield, Bristol B57 0AG
GB; GB(Residence); GB(Nationality)
(Designated only for: US)

Patent Applicant/Inventor:

- DE FERRANTI Marcus
20 Gilston Road, London SW10 9SR; GB; GB(Residence); GB(Nationality); (Designated only for: US)
- ELLIOT Richard John
74 Limerston Street, London SW7 0HJ; GB; GB(Residence); GB(Nationality); (Designated only for: US)
- PANTER Nigel
19 Reculver Road, Herne Bay CT6 6LG; GB; GB(Residence); GB(Nationality); (Designated only for: US)
- PANTER Timothy
12 Filton Road, Horsfield, Bristol B57 0AG; GB; GB(Residence); GB(Nationality); (Designated only for: US)

Legal Representative:

- KAZI Ilya(et al)(agent)
Mathys & Squire, 100 Grays Inn Road, London WC1X 8AL; GB;

| | Country | Number | Kind | Date |
|-------------|---------|------------|-------|----------|
| Patent | WO | 200189142 | A2-A3 | 20011122 |
| Application | WO | 2001GB2112 | | 20010515 |
| Priorities | US | 2000204341 | | 20000515 |
| | GB | 200028113 | | 20001117 |

Designated States: (All protection types applied unless otherwise stated - for applications 2004+)

[EP] AT; BE; CH; CY; DE; DK; ES; FI; FR; GB;
GR; IE; IT; LU; MC; NL; PT; SE; TR;

[OA] BF; BJ; CF; CG; CI; CM; GA; GN; GW; ML;
MR; NE; SN; TD; TG;

[AP] GH; GM; KE; LS; MW; MZ; SD; SL; SZ; TZ;
UG; ZW;

[EA] AM; AZ; BY; KG; KZ; MD; RU; TJ; TM;

Publication Language: English
Filing Language: English
Fulltext word count: 22895

Detailed Description:

...ISP or major network is slightly more complex.

The communication between AS networks is BGP. Each network would take its own set of connections to other ISP's through peering and transit links, and build a combined BGP route table which is the best routes from all the networks. This situation is not...

NPL

11/5/2 (Item 1 from file: 34) [Links](#)

Fulltext available through: [STIC Full Text Retrieval Options](#)

SciSearch(R) Cited Ref Sci

(c) 2008 The Thomson Corp. All rights reserved.

09905580 Genuine Article#: 463LJ Number of References: 6

Direction of next generation Internet eXchanges

Author: Nakagawa I (REPRINT) ; Hayashi E; Takahashi T

Corporate Source: INTEC Web & Genome Informat Corp,Toyama 9300804//Japan/ (REPRINT); INTEC

Web & Genome Informat Corp,Toyama 9300804//Japan/; Reitaku Univ,Kashiwa/Chiba 2778686/Japan/

Journal: IEICE TRANSACTIONS ON COMMUNICATIONS , 2001 , V E84B , N8 (AUG) , P 1989-1995

ISSN: 0916-8516 Publication date: 20010800

Publisher: IEICE-INST ELECTRONICS INFORMATION COMMUNICATIONS ENG , KIKAI-SHINKO-KAIKAN BLDG MINATO-KU SHIBAKOEN 3 CHOME, TOKYO, 105, JAPAN

Language: English Document Type: ARTICLE

Geographic Location: Japan

Journal Subject Category: ENGINEERING, ELECTRICAL & ELECTRONIC; TELECOMMUNICATIONS

Abstract: In this article, we survey current and next generation IX (Internet eXchange) technologies. An IX is a mechanism to interconnect many networks to each other. In other words, an ISP can establish 'peerings' with other ISPs by connecting their routers into IXes. First, we describe the basic IX model, including a policy model, called the 'bilateral' model, which allows participating ISPs to control routing policy and traffic on a 'peer' basis. Next, we classify current IX architectures from a technical point of view and discuss issues of current IXes. In the latter portion of this article, we describe next generation IX technologies, which achieve new features for IXes, such as: enabling larger volume traffic exchange with optical technology, providing virtual private peerings, migrating data-link media to participate into an IX, and exchanging traffic over widely distributed areas. We survey cutting-edge technologies for next generation IXes, and discuss the future of IX technology.

Descriptors--Author Keywords: Internet eXchange ; interconnection ; peering ; BGP 4

Cited References:

ASHWOODSMITH P, 2001, IETP INTERNET DRAFT

BLANCHET M, 2001, IETF INTERNET DRAFT

HUSTON G, 1999, V2, INTERNET PROTOCOL J

MANNING B, EXCHANGE POINT INFOR

REKHTER Y, 1995, BORDER GATEWAY PROTO

ROSEN E, 1999, IETF INTERNET DRAFT

14/5/2 (Item 1 from file: 2) [Links](#)

Fulltext available through: [STIC Full Text Retrieval Options](#)

INSPEC

(c) 2008 Institution of Electrical Engineers. All rights reserved.

05887136 INSPEC Abstract Number: B9504-6150P-010, C9504-5630-006

Title: Routing arbiter architecture

Author Estrin, D.; Postel, J.; Rekhter, Y.

Author Affiliation: Dept. of Comput. Sci., Univ. of Southern California, Los Angeles, CA, USA

Journal: *ConneXions* vol.8, no.8 p. 2-7

Publication Date: Aug. 1994 Country of Publication: USA

ISSN: 0894-5926

Language: English Document Type: Journal Paper (JP)

Treatment: Practical (P)

Abstract: As the Internet has evolved and grown, a key element has been the provision of stable routing information. An essential element of this has been the configured networks information assembled by MERIT and used in the NSFNET backbone routers. This configured networks information is used to control the dynamic routing information exchange among the NSFNET backbone and the attached networks. The Internet is entering a new phase with a new architecture brought about by changes in NSF support. In the new architecture, the provision of stable routing information will be much more complex. A new routing arbiter is to be developed to process the topology, connectivity, and routing policy information to create and distribute a stable master routing table. In addition, the routing arbiter will plan for, develop and deploy new routing services, such as multicast and adaptive alternate path routing. The new NSF architecture will consist of: a very high-speed backbone service (the vBNS); other network service providers (NSPs), including both the equivalent of today's regionals as well as other commercial service providers; network attachment points, whereby NSPs connect to the vBNS and to one another; stub networks, which will connect to their choice of NSPs; and the routing arbiter, which will manage the routing process for the Internet. In this article, we describe the architecture of the routing arbiter. (11 Refs)

Subfile: B C

Descriptors: data communication equipment; Internet; internetworking; network topology; telecommunication network routing

Identifiers: routing arbiter architecture; Internet; stable routing information; configured networks information; NSFNET backbone routers; dynamic routing information exchange; network topology; connectivity; routing policy information; stable master routing table; routing services; multicast; adaptive alternate path routing; NSF architecture; vBNS; very high-speed backbone service; network service providers; network attachment points; stub networks

Class Codes: B6150P (Communication network design and planning); B6210L (Computer communications); C5630 (Networking equipment); C5620W (Other computer networks)

Copyright 1995, IEE